

# 1S0FA0

## 4 BURNER GAS RANGE

Burner gas boiling range made of AISI 304 stainless steel, 20/10 mm thickness top. Top grids and burners in enamelled cast iron. Valve controlled removable burners with double crown burner cap. Pilot light and thermocouple. Pressed and sealed burner recess.



Power supply	Gas	Product fitting up	Counter Top
Worktop thickness	2 mm		

### Functional features

- Gas cooking top equipped with n. 4 open burners.
- n. 3 open burners with double-crown burner cap diam. 110 mm rated 6.5 kW with continuous power regulation from 6.5 to 1.9 kW.
- n. 1 open burner with single-crown burner cap diam. 80 mm rated 4 kW with continuous power regulation from 4 to 1.3 kW.
- Burners coupling in ceramic material for easy extraction.
- Burners and cast iron pan grids easily removable and washable.
- Burner Venturi tube with a innovative shape that guarantees an optimal combustion and safeguards the injector from plugging.
- The double crowned burner and the particular inclination of the flame ensure a better uniformity and thermal distribution on the bottom even of large pots.
- Pre-set appliance for installation on under compartment, support surface; with specific accessories on bridge solution and cantilever on beam.

### Constructional features

- Work top made in AISI 304 stainless steel, 20/10 thickness with Scotch Brite finish.
- Control panel made in AISI 304 stainless steel, thickness 12/10 mm, Scotch-Brite finish. Side paneling made in AISI 304 stainless steel, back panel in stainless steel.
- Side-by-side top juxtaposition very rigid and accurate guaranteeing max quality and hygiene.
- Pressed burner surround (one for each pair of burners), depth 71 mm, with large corners for easy cleaning.
- Pilot light of the top burners with protection to avoid accidental quenching by liquid spill.
- Top burners, burner cap and pan grids made in enamelled cast iron.
- Metal ergonomic knobs with rubber protection against water infiltration.
- Radiused rear splashback on the worktop h = 4 cm.
- Non-slip rubber feet h = 2 cm.
- Access to all components through front compartment or control console.

### Safety equipment and approvals

- Security control on gas operation ensured by thermostatic valve, pilot light and thermocouple.
- CE approvals in respect of all directives and regulations.
- Approval to European Standard EN 1672-2 Hygienic Design.

### Optional

- Smooth or ribbed griddle made of antacid semigloss cast iron.
- Central fireproof reduction disc useful for pans with diameter less than 10 cm.
- Grid made in round AISI 304 stainless steel, Ø 12 mm. Useful for 2 open burners.
- Burner surrounds for easy cleaning.

### Technical Data

Gas Power	23,5 kW	Dimensions	80x72x25 cm
Packing	86x82x65 cm		

4 BURNER GAS RANGE  
Icon7000 prof.700